CLAIMS:

We claim:

- 5 1. An adapter comprising:
 - (a) a first and a second surface;
 - (b) at least one first interconnect on the first surface,
 - (c) at least one second interconnect on the second surface;
 - (d) at least one connective path between the first and second interconnects, and
 - (e) a signal modifying circuit between the first interconnect and the second interconnect.
 - 2. The adapter of Claim 1 wherein the first set of interconnects are physically spaced to correspond to a first pin configuration of a power module.
 - 3. The adapter of Claim 1 wherein the second set of interconnects are physically spaced to correspond to a second pin configuration of an end user's circuit board.
 - 4. The adapter of Claim 1 wherein a signal modifying circuit acts upon an input to the adapter.
 - 5. The adapter of Claim 1 wherein a signal modifying circuit acts upon an output to the adapter.
 - 6. The adapter of Claim 2 wherein the power module is a DC-to-DC converter.
 - 7. The adapter of Claim 2 wherein the power module is an AC-to-DC inverter.
 - 8. The adapter of Claim 2 wherein the power module is a DC-to-AC inverter.
- 30 9. The adapter of Claim 1 wherein the first interconnects comprise surface mount connects.

25

10

Patent Application
Docket Number: AINNO.0102
Page 9 of 11

5

- 10. The adapter of Claim 1 wherein the first interconnects comprise through hole connects.
- 11. The adapter of Claim 1 wherein the second interconnects comprise surface mount connects.
- 12. The adapter of Claim 1wherein the second interconnects comprise through hole connects.
- 13. The adapter of Claim 1 wherein the second interconnects comprise a filter.
- 10 14. The adapter of Claim 1 wherein the second interconnects comprise an overvoltage protection device.